

Standalone Type Network Video Recorder

IP Standard + IP Megapixel DVR



Manage up to 4 / 8 / 16 Network Cameras Compatible with Major Brand Camera High Quality Live/Playback Video Export Playback Videos to AVI Web-based E-map Event Alert Smart Camera Search Mobile Devices Remote Monitoring

Pure Web Based Administration Two-way Audio Support External UPS

NVR: Network Video Recorder

The PRO Mega Network Video Recorder is designed for use within a surveillance system, and performs recordings and playbacks pictures from network cameras in the system. It is designed for small scale applications such as retail store and the system is expandable for multi-sites management with the bundled CMS software. Up to 16 cameras can be connected via a network and it is possible to record their camera pictures. It is possible to perform the settings or operate the NVR using a web browser installed on a PC connected to a network and live videos can be viewed on major mobile devices through its web browser. Recorded video can be played back from remote site by a PC. Up to 4 PCs (web browsers) can access this unit concurrently and it is possible to perform the settings and operate this unit. The PRO Mega Network Video Recorder is compatible with most major brand cameras and its ability to automatically search and find the available cameras on the network can greatly reduce the user effort when expanding the system

Specifications

CPU and Memory ARM9 500Mhz/128MB DDR RAM

Ethernet 10BaseT / 100BaseT/1GBaseT and half duplex/full duplex auto-negotiation

HDD SATA HDD Slot x 2, Max. Capacity 1TB per disk LED Cameras/Power/System/Network/HD/Alarm

Buttons Reset/Power/Buzzer

Connectors USB x 2 / RS-485 / DI/DO Connectors / RS-232

Power 19V DC / Power consumption: 90W Dimensions 220 x 215 x 81 mm

Weight 10l lbs (HDD not included) Temperature Operating: $5 ^{\circ}\text{C} \sim 45 ^{\circ}\text{C}/41 ^{\circ}\text{F} \sim 113 ^{\circ}\text{F}$

Storage: -40 °C ~ 70 °C/-14 °F ~ 158 °F

Humidity 5% ~ 90% (non condensing)
Safety FCC Class A/CE/UL

Cameras

Support Axis / Sony / Panasonic / AVTech / ACTi / D-Link / Canon / AMTK

Vivotek / Zavio / Prime Pro Mega

•Add Camera: Manual / Smart IP Search

•Max. Channel: 16

■ Video

Compression: MJPEG/MPEG-4 Part 2/H.264

Resolution: HD/MegaPixel/FD1/CIF/QCIF, or depends on camera

Max. Frame Rate: 120 fps (2 MegaPixel, H.264)

■ Audio

Streaming: Two-way audio

■ Live View

Display Mode: Live View/Playback/Full Screen

Split Screen: 1/4/8/16 Full Screen: up to 16 videos

PTZ Support: Virtual PTZ Panel/Auto Pan/Preset Point/Preset Sequence Sequence Mode: Sequence All/Manually Selected Cameras in 1/4/8/16 split view

with configurable time interval

Snapshot: Video Snapshot in JPEG format

■ Playback

Split Screen: 1/4/8/16

Search Method: Time/Date, Event with thumbnails

Playback Controls: Play/Pause/Stop/Forward/Reverse/Speed Adjustable Forward

and Rewind/Frame by Frame Forward
AVI Export: Export recorded files to AVI format

■ Network

Protocols: HTTP/SMTP/DHCP server and client/ARP/NTP/DNS/UPnP/FTP Streaming Protocols: Depends on the supported cameras

■ Recording

Capacity: Depends on Hard Disk

Recording Mode: Manual/Continuous/Scheduling/Event

Schedule Types: Manual Select/Day Mode/Night Mode/Weekend Mode

User Management

Management: User/Group

Number of Groups: 7 (administrator/Guest/User define x 5) Privileges: Live View/Playback/System Configurations/Camera

Configurations/Recording Configuration/Event Configuration/Maintenance

■ Triggers & Events

System Event -- System Start/Shutdown, System Settings Modified, Camera

Settings Modified, Start Recycle, Disk Full Camera Events -- Motion/Sensor Detection Event Actions: HTTP/Mail/FTP/Buzzer/Record Event Recording: Pre/Post Event Recordings

